

**NIKKOR Z****17-28mm f/2.8****JOURNEY WIDE**

From epic views to frame-filling close-ups. Take it all in with the lightweight ultra-wide-angle zoom lens that goes where you go. Superb up close. Brilliant in available light. The NIKKOR Z 17-28mm f/2.8 puts intriguing compositions and bold perspectives firmly within your grasp.

FEATURES

ULTRA-WIDE 17-28MM ZOOM RANGE

Landscapes to cityscapes. Expansive skies to street scenes. Architecture to interiors. You get superb sharpness and less distortion—even when shooting at the ultra-wide 17 mm end of the zoom range.

SHORT CLOSE-FOCUSING DISTANCE

A minimum focus distance of just 0.19 m enables sharp, clear results at close quarters. Fill the frame with intriguing details shot from your unique point of view.

FAST F/2.8 CONSTANT APERTURE

Maintains consistent exposure across the zoom range. Great for shooting in available light—or working creatively with shutter speeds and depth of field.

BIG BEAUTIFUL BOKEH

You get large, soft spheres of bokeh when shooting wide open, and bokeh is accentuated when shooting at close distances.

GREAT FOR VIDEO TOO

Videos won't be ruined by focusing sounds. Focus breathing is dramatically reduced so you can smoothly shift focus while maintaining framing.

CONFIDENT FOCUSING

AF is fast, smooth, quiet, and precise. The lens will focus quickly on your main subject—whether it's positioned in the foreground or the background.

EASY CONTROL

You can customise the silent control ring for the way you shoot. The wide zoom ring is simple to operate when you have your eye to the viewfinder.

GOES WHERE YOU GO

This lens is so light, you can keep it on your camera as you wander. Full sealing prevents dust and water droplets from getting between you and a great image.¹

¹ This lens is not guaranteed to be dust- and drip-resistant in all situations and under all conditions.

LENS HOOD HB-107

Bayonet lens hood designed specifically for use with the NIKKOR Z 17-28mm f/2.8. Minimises stray light and reduces flare.

INCLUDED ACCESSORIES



LENS CAP LC-67B



LENS CAP LF-N1



LENS HOOD HB-107



LENS CASE CL-C1



NIKKOR Z 17-28mm f/2.8

CAPTURE TOMORROW

TECHNICAL SPECIFICATIONS NIKKOR Z 17-28mm f/2.8

Mount	Nikon Z mount
Format	FX
Focal length	17-28 mm
Maximum aperture	f/2.8
Minimum aperture	f/22
Lens construction (elements - groups)	13 elements in 11 groups (including 2 ED glass elements, 1 Super ED glass elements and 3 aspherical lens elements)
Angle of view	FX format: 104°-75°, DX format: 79°-53°
Focal length scale	Graduated in millimeters (17, 20, 24, 28 mm)
Focusing system	Internal focusing (IF) system
Diaphragm blades	9 (rounded diaphragm opening)
Aperture system	Automatic aperture with electromagnetic diaphragm mechanism
Aperture range	f/2.8 to f/22
Minimum focus distance	0.19 m from focal plane (at 17 mm zoom position)
Maximum reproduction ratio	0.19×
Weight	Approx. 450 g
Maximum diameter × length (distance to end of lens from camera lens mount flange)	Approx. 75 mm x 101 mm
Filter-attachment size	67 mm
AF drive motor	Stepping motor (STM)
Supplied accessories	LC-67B Lens Cap (front cap), , LF-N1 Lens Cap (rear cap), HB-107 Lens Hood, CL-C1 Lens Case
Compatible accessories	67 mm screw-on filters (optional)
EAN code	4960759910332
SAP code	JMA718DA

Nikon will not be held liable for any errors this leaflet may contain. The appearance of this product, its specifications, and performance are subject to change without prior notice. September 2022. © Nikon Corporation.



© Alberto Seabra

CAPTURE TOMORROW

NIKKOR Z
17 - 28 mm f / 2.8

17-28MM ULTRA-WIDE ZOOM | F/2.8 FIXED APERTURE | FX MIRRORLESS | SILENT AF | LIGHTWEIGHT

